

24 Aug 2026

TEST REPORT

DIATOMACEOUS EARTH FILTER AID (HYFLOW SUPERCCELL)

CHARACTERISTICS	RESULTS
△ TYPE	FLUX-CALCINED DIATOMITE
△ MAX WT% RETAINED ON 140 SIEVE	8.0
△ MAX WT% RETAINED ON 325 SIEVE	27.0
△ PERMEABILITY (PFRV)	85-105 (0.72-1.1 DARCY)
△ PH (10% SLURRY)	8.0-11.0
◇ MOISTURE CONTENT	< 0.5%

(This report is computer generated and therefore does not require any signature.)

(For industrial use only. Not for fertilizer/oral/food or medical use)
(Marketed by Suraj Chemicals, manufactured by independent or contracted third-party facilities)

"ACIDS, SOLVENTS, MINERALS, BASES AND SPECIALISED CHEMICAL COMPOUNDS"

+91 - 7092722822, +91 - 9840284032
+91 - 44 - 25393652, 42130281
sales@surajchemicals.com
surajchemicals@yahoo.com

No 92, Govindappa Naicken Street
Shiva Complex, Chennai - 600001
www.surajchemicals.com
GST NO : 33ACEPV8190L1ZZ

EXCLUSIVE FOR GRASIM INDUSTRIES (ADITYA BIRLA), BASF (GERMANY), GODREJ INDUSTRIES, SNF (FRANCE)